



Certificate of Compliance
Argos Florida Super Masonry Cement Type S

January 4, 2024

This is to certify that each bag of Argos Florida Super Masonry Type S Masonry Cement as manufactured by Argos at its Newberry, FL plant, fully complies with ASTM specification C91. It contains an interground additive that affords a level of water repellency which at 2 grams, is well below the absorption requirement of Federal Specification SS-C-181-e which allows a maximum of 5 grams increase in weight of a 2 inch laboratory mortar cube in one hour. By so doing the resultant mortar will exceed the property requirements of ASTM C270, Table 2, provided that all the stated ingredients are mixed and tested in full accordance with all of the applicable provisions of ASTM C270.

Argos masonry cements are recommended to be mixed in a mechanical mixer at a volumetric ratio of one cubic foot (1 bag) masonry cement to not less than 2 ¼ and not more than 3 ft³ of damp, loose masonry sand conforming to ASTM C144 and an amount of clean, potable water to produce a workable consistency.

Please note that ASTM C270 is a laboratory test procedure only and is specifically not to be used to determine mortar strengths or other properties through field-testing. For field testing procedures, refer to ASTM C780.

Limited Warranty

Argos warrants that Argos Cements meet applicable ASTM requirements. Argos makes no other warranty, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY of merchantability or fitness for a particular purpose, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Having no control over their use, Argos will not guarantee finished work in which these products are used.

A handwritten signature in black ink that reads "Bill Kjorlien". The signature is written in a cursive, slightly slanted style.

Bill Kjorlien
Masonry Technical Service Manager
Argos USA LLC
bkjorlien@argos-us.com; (404) 307-5992