



Date:
Customer:
Project:
Location:
General Contractor:
Color: **Type N Superbond™ Mortar Cement**

Certificate of Compliance

Type N Superbond™ Mortar Cement Manufactured at Argos Atlanta, GA Plant

Argos USA LLC hereby certifies that each bag of Argos Type N Superbond™ Mortar Cement manufactured by Argos, fully complies with ASTM specification C1329.

Superbond™ Mortar Cement is recommended to be mixed in a mechanical mixer at a volumetric ratio of one cubic foot (1 bag) mortar cement to not less than 2 ¼ and not more than 3 ft³ of damp, loose masonry sand conforming to ASTM C144 and an amount of clean, potable water to produce a workable consistency. By so doing the resultant mortar will exceed the property requirements of ASTM C270, Table 2, provided that all the stated ingredients are mixed and tested in full accordance with all of the applicable provisions of ASTM C270.

Please note that ASTM C270 is a laboratory test procedure only and is specifically not to be used to determine mortar strengths or other properties through field-testing. For field testing procedures, refer to ASTM C780.

Limited Warranty

Argos warrants that Argos Cements meet applicable ASTM requirements. Argos makes no other warranty, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY of merchantability or fitness for a particular purpose, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Having no control over their use, Argos will not guarantee finished work in which these products are used.

A handwritten signature in black ink that reads "Bill Kjorlien".

Bill Kjorlien
Masonry Technical Service Manager
Argos USA LLC
bkjorlien@argos-us.com; (404) 307-5992